

MU Pigtail

Applications:

- CATV
- Video
- Active Device Termination
- Premise Installations
- Telecommunication Networks
- Local Area Networks (LANs)
- Data processing networks
- Wide Area Networks (WANs)
- Industrial, medical & military



Features:

- NTT-MU hardware compatibility
- NTT & JIS compliance
- Compact, pull-proof design
- High precision alignment
- One piece construction
- Tunable zirconia connector ferrule
- Corrosion resistant body
- UL-Rated plastic housing and boot
- Universal Duplex Clip
- Low insertion loss & back reflection

Specifications:

- PC , UPC or APC polishing
- Fiber Standard : Single Mode (ITU-T G.652) , Multimode (ITU-T G.651)
- Standard : Telcordia GR-326-CORE
- Cable diameter : 3.0mm or 2.0mm or 0.9mm
- Fiber type : 9/125 μ m , 62.5/125 μ m , 50/125 μ m or 10G
- Insertion loss : SM Less than 0.3dB , MM Less than 0.3dB
- Return loss : PC SM larger than 45 dB
UPC SM larger than 50 dB
APC SM larger than 60 dB
UPC MM larger than 20 dB
- Repeatability : Less than 0.2 dB
- Changeability : Less than 0.1 dB
- Operating temperature range : -40°C ~ 80°C
- Storage temperature range : -40°C ~ 80°C