


SC Patch Cord



APPLICATIONS

CATV	Active device termination
Metro	Local Area Networks (LANs)
Test equipment	Premise installations
Data processing networks	Wide Area Networks (WANs)
Telecommunication networks	

FEATURES

- Low insertion loss and back reflection loss
- Good exchangeability
- Good Durability
- High temperature stability
- Standard: Telcordia GR-326-CORE

AVAILABILITY

- Simplex/Duplex patch-cord available
- Fan-out available
- Pigtail available
- Various boot (cable) sizes available

SPECIFICATIONS

	Single mode	Multimode
Insertion Loss	Typical ≤ 0.2 dB, Maximum ≤ 0.3 dB	≤ 0.25 dB
Return Loss	≥ 50 dB (PC) ≥ 65 dB (APC)	
Repeatability	≤ 0.1	
Durability	≤ 0.2 dB typical change, 1000 matings	
Interchangeability	≤ 0.2 dB	
Tensile strength	> 70 N	
Operating Temperature	-40 to + 85 °C	-40 to + 85 °C

ORDERING OPTIONS

Connector Color	Boot (cable) Size	Boot Color	Fiber Type	Cable number	Application	Length
Beige	0.9mm	Blue	9/125 μ m (SM)	Simplex	PC	Customized
Blue	2.0mm	Green	50/125 μ m(MM)	Duplex	APC	
Green	3.0mm	Gray	62.5/125 μ m(MM)	Fan-out (4f)		
		Red		Fan-out (6f)		
		White		Fan-out (8f)		
				Fan-out (12f)		